

## G2-LXP2-RS2

~8.5° spot beam with light, black holder.  
Assembly with installation tape.


### TECHNICAL SPECIFICATIONS:

Dimensions	Ø 21.8 mm
Height	14.7 mm
Fastening	tape
Colour	black
Box size	480 x 280 x 300 mm
Box weight	8.1 kg
Quantity in Box	1680 pcs
ROHS compliant	yes ⓘ



### MATERIAL SPECIFICATIONS:


Component	Type	Material	Colour
LXP2-RS2	Lens	PMMA	
LXP2-LT-HLD	Holder	PC	black
HEIDI-TAPE	Tape	Acrylic tape	black



**PHOTOMETRIC DATA (MEASURED):**



**CREE** 

LED XP-E  
FWHM 7.0°  
Efficiency 88 %  
Peak intensity 34.650 cd/lm  
Required components:




**CREE** 

LED XP-L  
FWHM 14.0°  
Efficiency 88 %  
Peak intensity 9.500 cd/lm  
Required components:



**CREE** 


LED XP-L HI  
FWHM 8.0°  
Efficiency 89 %  
Peak intensity 20.100 cd/lm  
Required components:




#### PHOTOMETRIC DATA (SIMULATED):




LED XP-E2  
 FWHM 10.0°  
 Efficiency 94 %  
 Peak intensity 24.600 cd/lm  
 Required components:




LED XP-G2  
 FWHM 10.0°  
 Efficiency 93 %  
 Peak intensity 22.400 cd/lm  
 Required components:



LED XT-E  
 FWHM 9.5°  
 Efficiency 92 %  
 Peak intensity 19.900 cd/lm  
 Required components:




LED H35C1 (LEMWA33)  
 FWHM 10.0°  
 Efficiency 92 %  
 Peak intensity 19.400 cd/lm  
 Required components:



#### PHOTOMETRIC DATA (SIMULATED):




LED NVSxx19B/NVSxx19C  
FWHM 11.0°  
Efficiency 88 %  
Peak intensity 15.000 cd/lm  
Required components:




### SAMSUNG

LED LH351A(3535)  
FWHM 9.0°  
Efficiency 91 %  
Peak intensity 21.600 cd/lm  
Required components:




### SAMSUNG

LED LH351B  
FWHM 10.0°  
Efficiency 91 %  
Peak intensity 17.200 cd/lm  
Required components:




SEOUL SEMICONDUCTOR

LED Z5M1/Z5M2  
FWHM 10.0°  
Efficiency 93 %  
Peak intensity 20.500 cd/lm  
Required components:



### PHOTOMETRIC DATA (SIMULATED):



### GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

### MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### LEDiL Oy

Joensuunkatu 13  
FI-24240 SALO  
Finland

#### LEDiL Inc.

228 West Page Street  
Suite D  
Sycamore IL 60178  
USA

#### Local sales and technical support

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)

#### Shipping locations

Salo, Finland  
Hong Kong, China

#### Distribution Partners

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)