


Part Number: 5222FL



Fire Alarm, #16-4c BC, Shielded, FPLR

# **Product Description**

Fire Alarm Cable, Riser-FPLR, 4-16 AWG solid bare copper conductors with polyolefin insulation, overall Beldfoil® shield, PVC jacket with ripcord

# **Technical Specifications**

## **Product Overview**

Suitable Applications:	Fire Protection, Alarm, Signal, Monitor/Detection, Audio Circuits, Control Circuits, Initiating Circuits, Notification Circuits

## **Physical Characteristics (Overall)**

#### Conductor

AWG	Stranding	Material	No. of Conductors
16	Solid	BC - Bare Copper	4
Condu	ctor Count:		4
Condu	ictor Size:		16 AWG

#### Insulation

Material	Nominal Wall Thickness
PP - Polypropylene	0.007 in

# Color Chart

Number	Color
1	Black
2	Red
3	Brown
4	Blue

# Outer Shield Material

Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Aluminum/Polyester	Beldfoil®	100 %	TC - Tinned Copper	24	Solid

### **Outer Jacket Material**

Material	Nominal Diameter	Nominal Wall Thickness	Ripcord
PVC - Polyvinyl Chloride	0.197 in	0.017 in	Yes

## **Construction and Dimensions**

# Cabling



## **Electrical Characteristics**

#### Conductor DCR

Nominal Conductor DCR	Nominal Outer Shield DCR
3.9 Ohm/1000ft	7.2 Ohm/1000ft

## Capacitance

32.5 pF/ft	58.5 pF/ft
Shielding:	Foil(s) or Copper Tape(s)

#### Current

Max. Recommended Current [A]
5 Amps per conductor @ 25°C A

## Voltage

UL Voltage Rating 300 V RMS

## **Temperature Range**

UL Temp Rating:	75°C
Operating Temp Range:	-20°C To +75°C

#### **Mechanical Characteristics**

Bulk Cable Weight:	43 lbs/1000ft
Max Recommended Pulling Tension:	138.8 lbs
Min Bend Radius/Minor Axis:	2 in

#### **Standards**

NEC Articles:	760	
NEC/(UL) Specification:	FPLR	
Other Specification:	California State Fire Marshall	

## **Applicable Environmental and Other Programs**

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

## Flammability, LS0H, Toxicity Testing

UL Flammability:	UL1666 Riser
CSA Flammability:	FT4
UL voltage rating:	300 V RMS

## Plenum/Non-Plenum

Plenum (Y/N):	No
Plenum Number:	6222FL

### **Part Number**

#### Variants



### © 2018 Belden, Inc

## All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.