

Connector set - HC-EVO-B10PT-BWSC-HL-M25ELC-AL - 1411491

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



EVO connector set, B10 series, metal housing, consisting of sleeve housing 1411456, panel mounting base 1411321, EVO screw connection 1411446, push-in contact inserts: 1407729, 1407730



Key Commercial Data

Packing unit	1 STK
GTIN	4 046356 932912
GTIN	4046356932912

Technical data

General

Number of positions	10+PE
Туре	B10
Connection method	Push-in connection
Cable outlet	straight
	lateral
Degree of protection for housing	IP66
	IP67
	4 (UL 50e)
	4X (UL 50e)
	12 (UL 50e)
Connection method	Push-in connection
Rated voltage (III/3)	500 V
Rated surge voltage	6 kV
Rated current	16 A

Standards and Regulations

Flammability rating according to UL 94	V0

Environmental Product Compliance



Connector set - HC-EVO-B10PT-BWSC-HL-M25ELC-AL - 1411491

Technical data

Environmental Product Compliance

REACh SVHC	Lead 7439-92-1

Drawings

Schematic diagram




Schematic diagram




Pin assignment, connection side, pin

Diagram



Pin assignment, connection side, socket


Dimensional drawing



Derating diagram

Dimensional drawing

Dimensional drawing



Mounting cutout



Connector set - HC-EVO-B10PT-BWSC-HL-M25ELC-AL - 1411491

Articles in set

Contact insert - HC-B10-I-PT-F - 1407729



HEAVYCON socket insert, B10 series, 10 + PE-pos., push-in connection

Contact insert - HC-B10-I-PT-M - 1407730



HEAVYCON pin insert, B10 series, 10 + PE-pos., push-in connection

Housing - HC-EVO-B10-HLFS-EL-AL - 1411456



HEAVYCON EVO sleeve housing, EMC version, without powder coating, with bayonet flange for EVO screw connection, B10, for single locking latch, height: 64 mm, without EVO screw connection.

Housing - HC-STA-B10-BWSC-ELC-AL - 1411321



HEAVYCON panel mounting base, B10, with single locking latch, with plastic protective cover, with flat gasket, salt-water-resistant aluminum, conductive profile gasket.

Cable gland - HC-B-G-M25-EC-AL - 1411446



EVO EMC cable gland with bayonet locking, B series, size M25, cable diameter: 11 - 16 mm

Approvals

Approvals

Approvals



Connector set - HC-EVO-B10PT-BWSC-HL-M25ELC-AL - 1411491

Approvals Ex Approvals Approval details EAC III GL GL http://exchange.dnv.com/tari/ 6196614 HH

Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300

Fax +49 5235 300

http://www.phoenixcontact.com