

## CD-HF 80X25


Order No.: 3240356



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=3240356>

Wiring channel, gray, halogen-free, consisting of upper and lower part,  
width: 80 mm, height: 25 mm, length: 2000 mm

### Commercial data

GTIN (EAN)	 4 046356 508414
Note	Made-to-order
sales group	B204
Pack	12 pcs.
Customs tariff	39259020
Catalog page information	Page 101 (NTK-2010)

### Product notes

WEEE/RoHS-compliant since:  
05/05/2009



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

### Technical data

#### General

Length (b)	2000 mm
Height	25 mm
Width (a)	80 mm
Color	gray
Base element material	ABS-PC

Inflammability class acc. to UL 94	V0
Ambient temperature (operation)	-25 °C ... 90 °C
Components	Halogen-free
Material	PC/ABS

**Certificates / Approvals**



Certification CSA, UL, VDE-PZI

**Accessories**

Item	Designation	Description
<b>General</b>		
3240284	CD WR	Universal wire holding bracket, perforated, for wiring channels
3240373	CD-HF COVER 80	Cover for wiring channel, gray, halogen-free, width: 80 mm, length: 2000 mm
3240498	RVT-PA 4	Plastic body-bound rivet, 4 mm diameter, for a material thickness of 1.5 ... 6 mm
3240499	RVT-PA 6	Plastic body-bound rivet, 6 mm diameter, for a material thickness of 1.5 ... 6 mm
1212478	UNIFOX-RVT P 4	Rivet setting tool, for use with RVT-PA 4 plastic body-bound rivets
1212509	UNIFOX-RVT P 6	Rivet setting tool, for use with RVT-PA 6 plastic body-bound rivets

**Address**

PHOENIX CONTACT Inc., USA  
586 Fulling Mill Road  
Middletown, PA 17057, USA  
Phone (800) 888-7388  
Fax (717) 944-1625  
<http://www.phoenixcon.com>



© 2011 Phoenix Contact  
Technical modifications reserved;